

Название публикации:

Structural and Mechanical Properties of PLA-Hydroxyapatite Composites Studied by the Scanning Impulse Acoustic Microscopy

Авторы:

Morokov, ES [1] ; Demina, VA [2] ; Sedush, NG [2,5] ; Khramtsova, EA [1] ; Zykova, AK [1,6] ; Grigoriev, TE [2,3,5] ; Petronyuk, YS [1,4] ; Chvalun, SN [2,5] ; Levin, VM [1]

[1] Russian Acad Sci, NM Emanuel Inst Biochem Phys, 4 Kosygin St, Moscow 119334, Russia

[2] Kurchatov Inst, Natl Res Ctr, 1 Akad Kurchatova Pl, Moscow 123182, Russia

[3] Russian Acad Sci, AN Nesmeyanov Inst Organoelement Cpds, 28 Vavilov St, Moscow 119991, Russia

[4] Russian Acad Sci, Sci & Technol Ctr Unique Instrumentat, 15 Butlerov St, Moscow 117342, Russia

[5] Moscow Technol Univ, Inst Fine Chem Technol, 86 Vernadskogo Prosp, Moscow 119571, Russia [

6] Plekhanov Russian Univ Econ, Stremyanny Per 36, Moscow 117997, Russia

Наименование журнала:

9TH INTERNATIONAL CONFERENCE ON TIMES OF POLYMERS AND COMPOSITES: FROM AEROSPACE TO NANOTECHNOLOGY

Отредактировано: DAmore, A; Acierno, D; Grassia, L

Серия книг: AIP Conference Proceedings

Том: 1981

Номер статьи: UNSP 020138

DOI: 10.1063/1.5046000

Опубликовано: 2018

Тип документа: Proceedings Paper

Аннотация:

Ultrasound methods have been applied for investigation of poly-L-lactide with hydroxyapatite composites. It was shown that this method allows to visualize the filler distribution in the polymer matrix, the compatibility of the filler with the polymer matrix, defects and artifacts. Sound velocity of longitudinal and transverse wave and elastic characteristic of the composites PLA+HA were obtained by high frequency ultrasound focused beam.

Ключевые слова:

composite materials; polylactide; biodegradable polymers; hydroxyapatite; mechanical characteristics; ultrasound; acoustic microscopy; sound velocity